



The Right Connection®

# BOSS LPS

## Low Pressure Systems

Products designed specifically for the oil and gas industry

### Vent-Lock Safety Cam and Groove Couplings



#### Application:

- transfer of fluids and solids with a safer disconnection

#### Features:

- safety release cam and groove couplings that permit the release of static pressure when disconnecting hose assembly
- venting system protects operator from hazardous or non-hazardous fluids or solids
- rated to **250 PSI**, recommendation based on the use of mating Dixon L-style fittings at ambient temperature (**70°F**) with standard Buna-N seal installed, for use at elevated temperature or other unusual operating conditions, consult Dixon does not interchange with standard cam and groove products use only with Dixon L-style fittings

#### Materials:

- 316 stainless steel
- consult Dixon or visit [dixonvalve.com](http://dixonvalve.com) for availability of other materials

#### Attachment:

- ferrules, sleeves, bands, and other reliable options

Size	Type A 316 Stainless Steel Part #	Type C 316 Stainless Steel Part #	Type E 316 Stainless Steel Part #	Type DC 316 Stainless Steel Part #	Type DP 316 Stainless Steel Part #
1"	L100-A-SS	L100-C-SS	L100-E-SS	L100-DC-SS	L100-DP-SS
2"	L200-A-SS	L200-C-SS	L200-E-SS	L200-DC-SS	L200-DP-SS

connect with us on



### Dixon

ph 877.963.4966  
fx 800.283.4966  
sales@dixonvalve.com  
dixonvalve.com

Printed in the USA

scan to visit our website

